This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific ISTOBA esens

legislation 53162XX_ XTRACT DRYING WAX PLUS

Date of	compilation: 16/03/2022	Revised: 20/10/2023	Version: 3 (Replaced 2)
SECT	TON 1: IDENTIFICATION	OF THE SUBSTANCE/M	IIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier:	53162XX_ XTF	RACT DRYING WAX PLUS
	Other means of identifica	ation:	
	UFI:	UP6X-P94V-10	606-2SYP
1.2	Relevant identified uses	of the substance or mixt	ure and uses advised against:
	Relevant uses: Wax polish. I	For professional users only.	
	Uses advised against: All use	es not specified in this section	on or in section 7.3
1.3	Details of the supplier of	the safety data sheet:	
	ISTOBAL, S.A AVDA. CONDE DEL SERRALL 46250 L'ALCUDIA - VALENC Phone: +34 96 299 79 40 - istobal@istobal.com https://www.istobal.com	IA - ESPAÑA	
	Imported in UK by: ISTOBAL 107 Mill Rd, Stourport-on-Severn DY13 9 United Kingdom T: +44 (0) 1299826967	BL,	
1.4	Emergency telephone nu	mber: UK: Call NHS 111 c EU: +32 3 575 55 !	
SECT	TION 2: HAZARDS IDENT	IFICATION **	
2.1	Classification of the subs		
	CLP Regulation (EC) No 1	L272/2008:	
	Classification of this product	has been carried out in acc	cordance with CLP Regulation (EC) No 1272/2008.
2.2	Acute Tox. 4: Acute toxicity,	Category 4, H302+H332 us to the aquatic environme mage, Category 1, H318	nt, long-term hazard, Category 3, H412
	CLP Regulation (EC) No 1 Danger	1272/2008:	



Hazard statements:

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Skin Irrit. 2: H315 - Causes skin irritation.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P280: Wear protective gloves/protective clothing/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of water. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a poison center/doctor. P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

** Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

53162XX_XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022 Revised: 20/10/2023

esens

Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

UFI: UP6X-P94V-1G06-2SYP

2.3 Other hazards:

ISTOBA

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of alcohols, colourants, glycol ethers and tensoactives

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS: 111-76-2		2-butoxyethanol ¹	2-butoxyethanol 1 ATP ATP18			
EC: Index: REACH:	203-905-0 603-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008	Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Danger 🛛 🛞	30 - <40 %		
CAS: Non-applicable EC: Non-applicable		Fatty acids, C18 unsatd. reaction products with triethanolamine, di-Me sulfate- guaternized ¹ Self-classified				
Index: REACH:	Non-applicable 01-2119472309-33- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	20 - <30 %		
CAS: 68155-07-7 EC: 268-935-9 Index: Non-applicable REACH: Non-applicable		Amides, C8-18 and C	18-unsatd., N,N-bis(hydroxyethyl) ¹ Self-classified			
		Regulation 1272/2008	Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	5 - <10 %		

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acut	Genus	
2-butoxyethanol	LD50 oral	1200 mg/kg (ATEi)	Rat
CAS: 111-76-2	LD50 dermal	Non-applicable	
EC: 203-905-0	LC50 inhalation	3 mg/L (ATEi)	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

53162XX XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

ISTOBA

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	45 °C
Maximum time:	18 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
2-butoxyethanol	IOELV (8h)	20 ppm	98 mg/m ³	
CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m ³	

DNEL (Workers):

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable
Fatty acids, C18 unsatd. reaction products with triethanolamine, di-Me sulfate-quaternized	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	312,5 mg/kg	Non-applicable
EC: Non-applicable	Inhalation	Non-applicable	Non-applicable	44 mg/m ³	Non-applicable

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

· · · · · · · · · · · · · · · · · · ·		· · · · ·			
	Short	exposure	Long	exposure	
Identification		Systemic	Local	Systemic	Local
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable
Fatty acids, C18 unsatd. reaction products with triethanolamine, di-Me sulfate-quaternized	Oral	Non-applicable	Non-applicable	7,5 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	187,5 mg/kg	Non-applicable
EC: Non-applicable	Inhalation	Non-applicable	Non-applicable	13 mg/m ³	Non-applicable

PNEC:

Identification				
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
Fatty acids, C18 unsatd. reaction products with triethanolamine, di-Me sulfate-quaternized	STP	2,96 mg/L	Fresh water	0,002 mg/L
CAS: Non-applicable	Soil	0,115 mg/kg	Marine water	0 mg/L
EC: Non-applicable	Intermittent	0,019 mg/L	Sediment (Fresh water)	0,58 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,058 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

If product is used at the concentration dosing conditions specified in the relevant instructions for use (section 15), personal protective equipment described in section 8.2 for UNDILUTED products will not be required.

Safe handling recommendations for undiluted product:

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E	Body protection				

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

ISTOBAL esens

53162XX_ XTRACT DRYING WAX PLUS

ION 8:	EXPOSURE	CONTR	OLS/PERSON	AL PROTECT	ION (continued)		
	Pictogram		PPE	Labelling		CEN Standard		Remarks
		w	ork clothing	CATI			perio recom	ce before any evidence of deterioration. ds of prolonged exposure to the product professional/industrial users CE III is mended, in accordance with the regulat ISO 6529:2013, EN ISO 6530:2005, EN 13688:2013, EN 464:1994.
		Anti-	slip work shoes	CAT II	E	ISO 20347:2012	perio recom	ce before any evidence of deterioration. ds of prolonged exposure to the product professional/industrial users CE III is mended, in accordance with the regulat EN ISO 20345:2012 y EN 13832-1:2007
F Add	ditional emerge	ency mea	asures					
	Emergency mea	isure	S	tandards		Emergency meas	ure	Standards
	Emergency sho	ower		ISI Z358-1)11, ISO 3864-4:20	011	Eyewash station	าร	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
	onmental exp					,	-	
Ave	D.C. density at a erage carbon n	umber:	6	84 kg/m³ (346	,84 g/l	L)		
Ave Ave	erage carbon n erage molecula	umber: r weight	6	2 g/mol	6,84 g/∣	L)		
Ave Ave	erage carbon n erage molecula : PHYSICAL A	umber: r weight AND CH	6 : 118,	2 g/mol		L)		
Ave Ave FION 9: Inform	erage carbon n erage molecula PHYSICAL A mation on bas	umber: r weight ND CH sic phys	6 : 118, IEMICAL PRO	2 g/mol PERTIES ical propertie		L)		
Ave Ave TION 9: Inforr For cor	erage carbon n erage molecula PHYSICAL A mation on bas	umber: r weight ND CH sic phys	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie		L)		
Ave Ave FION 9: Inforr For cor Appea	erage carbon n erage molecula : PHYSICAL A mation on bas mplete informa	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie	95:	L)		
Ave Ave TION 9: Inforr For con Appea Appea	erage carbon n erage molecula : PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance:	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie asheet. Liqu Trai	iid	nt		
Ave Ave TION 9: Inforr For coi Appea Physica	erage carbon n erage molecula : PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance:	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie asheet. Liqu Trai	es: iid	nt		
Ave Ave TION 9: Inforr For cor Appea Appea	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance:	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yell	iid	nt		
Ave Ave TION 9: Inforr For cou Appear Physica Appear Colour Odour:	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance:	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha	iid nspare ow-red racteri	nt		
Ave Ave TION 9: Inforr For cou Appear Physica Appear Colour Odour:	erage carbon n erage molecula : PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: : threshold:	umber: r weight AND CH sic phys tion see	6 : 118, IEMICAL PROI	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha	iid nspare ow-red racteri	nt I stic		
Ave Ave TION 9: Inforr For con Appear Colour Odour: Odour Volati	erage carbon n erage molecula : PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: : threshold:	umber: r weight AND CH sic phys tion see C:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha	iid nspare ow-rec racteri i-applic	nt I stic		
Ave Ave TION 9: Inforr For cor Appear Colour Odour: Odour: Volati Boiling	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: : threshold: lity:	umber: r weight AND CH sic phys tion see C: spheric p	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha Non	iid nspare ow-rec racteri i-applic	nt I stic		
Ave Ave TION 9: Inforr For cou Appear Odour: Odour: Odour: Odour Volati Boiling Vapou	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: threshold: lity: point at atmos	umber: r weight AND CH sic phys tion see C: C: spheric p 0 °C:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha Non 171 152	iid nspare ow-red racteri n-applic oC Pa	nt I stic		
Ave Ave TION 9: Inforr For cor Appear Colour Odour Odour Volati Boiling Vapour Vapour	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: threshold: ility: point at atmos r pressure at 20	umber: r weight AND CH sic phys tion see C: C: spheric p 0 °C: 0 °C:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha Non 171 152 968	iid nspare ow-rec racteri i-applic oC Pa ,09 Pa	nt I stic cable *		
Ave Ave TION 9: Inforr For cou Appear Odour: Odour: Odour: Odour: Dolati Boiling Vapour Vapour Evapor	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: threshold: lity: point at atmos r pressure at 20 r pressure at 20	umber: r weight sic phys tion see C: C: spheric p 0 °C: 0 °C: 0 °C:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha Non 171 152 968	iid nspare ow-rec racteri i-applic oC Pa ,09 Pa	nt I stic cable * (0,97 kPa)		
Ave Ave ION 9: Inforr For cou Appea Physica Appeaa Colour Odour: Odour: Odour Volati Boiling Vapour Vapour Evapor Produ	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: threshold: ility: point at atmos r pressure at 20 r pressure at 20 r pressure at 20 r ation rate at 20	umber: r weight sic phys tion see C: C: spheric p 0 °C: 0 °C: 0 °C:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yello Cha Non 171 152 968 Non	iid nspare ow-red racteri i-applid Pa ,09 Pa i-applid	nt I stic cable * (0,97 kPa)		
Ave Ave Ave Inforr For con Appear Odour Odour Odour Volati Boiling Vapour Vapour Evapor Produ Density	erage carbon n erage molecula PHYSICAL A mation on bas mplete informa arance: al state at 20 % rance: threshold: lity: point at atmos r pressure at 20 ration rate at 20 ration rate at 20 ration rate at 20 ration rate at 20	umber: r weight sic phys tion see C: C: Spheric p 0 °C: 0 °C: 0 °C: n:	6 118, IEMICAL PROI ical and chem the product dat	2 g/mol PERTIES ical propertie asheet. Liqu Tran Yellu Cha Non 171 152 968 Non 933	iid nspare ow-red racteri i-applid Pa ,09 Pa i-applid	nt I stic cable * (0,97 kPa) cable * kg/m ³		

Kinematic viscosity at 40 °C: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Non-applicable *

Kinematic viscosity at 20 °C:

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

53162XX_ XTRACT DRYING WAX PLUS

Date of	compilation: 16/03/2022 Revis	sed: 20/10/2023	Version: 3 (Replaced 2)	
SECT	TION 9: PHYSICAL AND CHEMIC	CAL PROPERTIES	5 (continued)	
	Concentration:		Non-applicable *	
	pH:		4 - 5 (at 100 %)	
	Vapour density at 20 °C:		Non-applicable *	
	Partition coefficient n-octanol/water	20 °C:	Non-applicable *	
	Solubility in water at 20 °C:		Non-applicable *	
	Solubility properties:		Non-applicable *	
	Decomposition temperature:		Non-applicable *	
	Melting point/freezing point:		Non-applicable *	
	Flammability:			
	Flash Point:		69 °C	
	Flammability (solid, gas):		Non-applicable *	
	Autoignition temperature:		238 °C	
	Lower flammability limit:		Non-applicable *	
	Upper flammability limit:		Non-applicable *	
	Particle characteristics:			
	Median equivalent diameter:		Non-applicable	
9.2	Other information:			
	Information with regard to phy	sical hazard clas	ses:	
	Explosive properties:		Non-applicable *	
	Oxidising properties:		Non-applicable *	
	Corrosive to metals:		Non-applicable *	
	Heat of combustion:		Non-applicable *	
	Aerosols-total percentage (by mass) components:) of flammable	Non-applicable *	
	Other safety characteristics:			
	Surface tension at 20 °C:		Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to the nature of the prod	uct, not providing infor	mation property of its hazards.	

10.1	Reactivity:									
10.2	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet. Chemical stability:									
	Chemically stable under the indicated conditions of storage, handling and use.									
10.3	Possibility of hazardous reactions:									
	Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.									
10.4	Conditions to avoid:									
	Applicable for handling and storage at room temperature:									
	Shock and friction Contact with air Increase in temperature Sunlight Humidity									
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable					
10.5	Incompatible materials:									
	Acids	Water	Oxidising materials	Combustible materials	Others					
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases					

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: 2-butoxyethanol (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

ISTOBAL

53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

Identification		Acute toxicity		Genus
2-butoxyethanol		LD50 oral	1200 mg/kg (ATEi)	Rat
CAS: 111-76-2		LD50 dermal	3000 mg/kg	Rabbit
EC: 203-905-0		LC50 inhalation	3 mg/L (ATEi)	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Amides, C8-18 and C18-unsatd., N,N-bis(hydroxyethyl)	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 68155-07-7	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 268-935-9	EC50	>1 - 10 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
2-butoxyethanol	BCF	3	
CAS: 111-76-2	Pow Log	0.83	
EC: 203-905-0	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-butoxyethanol	Кос	8	Henry	1,621E-1 Pa·m ³ /mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment: Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022

Revised: 20/10/2023

Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
20 01 29*	detergents containing hazardous substances	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Relevant instructions for use:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation

ISTOBAL Ser

53162XX_ XTRACT DRYING WAX PLUS

Date of compilation: 16/03/2022 Revised: 20/10/2023 Version: 3 (Replaced 2) SECTION 15: REGULATORY INFORMATION (continued) Dilute the pack in the Xtract Mixing System (1L product + 9L osmotized water). Use osmotized water, dosing 15mL/min. **Other legislation:** The product could be affected by sectorial legislation 15.2 Chemical safety assessment: The supplier has not carried out evaluation of chemical safety. SECTION 16: OTHER INFORMATION Legislation related to safety data sheets: The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878). Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Substances that contribute to the classification (SECTION 2): Removed substances 2-butoxyethanol (111-76-2) Amides, C8-18 and C18-unsatd., N,N-bis(hydroxyethyl) (68155-07-7) Texts of the legislative phrases mentioned in section 2: H315: Causes skin irritation. H318: Causes serious eye damage. H412: Harmful to aquatic life with long lasting effects. H302+H332: Harmful if swallowed or if inhaled. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 3: H331 - Toxic if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Éye Irrit. 2: H319 - Causes serious eye irritation. Skin Irrit. 2: H315 - Causes skin irritation. Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.